

## XPEL MODEL

MODEL	ENCUMBRANCE	LENGTH	HEIGHT	TRACTOR		HAMMERS	WEIGHT	P.T.O	SIDE SHAFT TRAVEL
				CV	kW				
				HP	kW				
XPEL 160	180	141	100	55/110	41/81	10	700	540	450
XPEL 180	200	141	100	60/110	44/81	11	750	540	450
XPEL 200	221	141	100	70/120	52/88	14	800	540	450
XPEL 220	240	141	100	75/120	55/88	14	850	540	450

## BVE MODEL

MODEL	ENCUMBRANCE	LENGTH	HEIGHT	TRACTOR		HAMMERS	WEIGHT	P.T.O	SIDE SHAFT TRAVEL
				CV	kW				
				HP	kW				
BVE 160	180	118	93	40/70	29/52	16	470	540	450
BVE 180	200	118	93	55/90	41/67	18	520	540	450
BVE 200	220	118	93	65/100	48/75	20	570	540	450
BVE 220	240	118	93	75/110	56/82	22	620	540	450

## FX MODEL

MODEL	ENCUMBRANCE	LENGTH	HEIGHT	TRACTOR		HAMMERS	WEIGHT	P.T.O	SIDE SHAFT TRAVEL
				CV	kW				
				HP	kW				
FX 100	120	85	87	18/30	13/22	6	205	540	Fixed
FX 120	139	85	87	25/40	18/29	7	230	540	Fixed
FX 140	160	105	88	30/55	22/41	9	315	540	Fixed
FX 160	183	110	93	40/70	29/52	10	395	540	Fixed
FX 180	203	110	93	55/75	41/55	11	425	540	Fixed
FX 200	223	110	93	65/85	48/63	16	460	540	Fixed

## VPE MODEL

MODEL	ENCUMBRANCE	LENGTH	HEIGHT	TRACTOR		HAMMERS	WEIGHT	P.T.O	SIDE SHAFT TRAVEL
				CV	kW				
				HP	kW				
VPE 180	200	114	106	55/85	41/63	11	680	540	1.000
VPE 210	229	114	106	70/110	52/81	14	780	540	1.000
VPE 240	257	114	106	80/120	59/88	16	850	540	1.000
VPE 270	292	114	106	80/130	66/96	17	950	540	1.000
VPE 300	320	114	106	95/140	70/104	20	1030	540	Fixed